

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
9 September 2005 (09.09.2005)

PCT

(10) International Publication Number
WO 2005/082486 A1

(51) International Patent Classification⁷: **B01D 46/00**

(21) International Application Number:
PCT/KR2004/000727

(22) International Filing Date: 30 March 2004 (30.03.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10-2004-0013963 2 March 2004 (02.03.2004) KR

(71) Applicant (for all designated States except US): **CONET INDUSTRIES INC.** [KR/KR]; 6-16 Yangjae-dong, Socho-gu, Seoul 137-130 (KR).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **SONG, Sung-Wook** [KR/KR]; 5-103 Kaepo-1-cha Woosung Apt., 503, Daechi-dong, Kangnam-gu, Seoul 135-280 (KR).


(74) Agent: **YOO, Dong-Ho**; Dong Ho Yoo Patent & Law Office, Rm. 903, Kangnam Bldg., 1321-1 Socho-dong, Socho-gu, Seoul 137-070 (KR).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,

[Continued on next page]

(54) Title: **AIR CLEANER**



(57) Abstract: The present invention relates to an air cleaner capable of quickly cleaning air in a larger area in an improved air circulation construction in which a body of an air cleaner is formed in a cylindrical shape, and air is sucked through an entire surface of a cylindrical body, and the sucked air is passed through a cylindrical filter and a cleaning unit, and the cleaned air is discharged in an upward direction, and in addition it is possible to prevent inlet air and outlet air from being mixed each other for thereby achieving an effective cleaning operation.

WO 2005/082486 A1

WO 2005/082486 A1



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— with international search report

AIR CLEANER

Technical Field

The present invention relates to an air cleaner, and in particular to an air cleaner that is characterized in that a body of an air cleaner is formed in a cylindrical shape, and air is sucked through an entire surface of a cylindrical body, and the sucked air is passed through a cylindrical filter and a cleaning unit, and the cleaned air is discharged in an upward direction.

Background Art

Generally, a conventional small-size air cleaner is hung on a wall or is installed on a table, and a large-size air cleaner is installed on the floor beside a wall.

Since the conventional air cleaner is designed to suck and discharge air in a forward direction, only the air near the air cleaner is cleaned and the air at a distance longer from the system is not cleaned.

In addition, since an air flow section for filtering, cleaning and discharging air is biased in one side, the cross sectional area of the filter is not wide. Therefore, the filter should be often cleaned, so that the life span of the filter is decreased.

The conventional air cleaner has only an air cleaning function without

an air sterilization function and a harmful gas removing function. Therefore, an ideal air cleaning is not operated.

Since the conventional air cleaner does not have a warm-air heating function, heating equipment is additionally needed when an indoor temperature is low. Therefore, in the conventional art, both the heating equipment and the air cleaner should be provided separately. In addition, there is not a remote control function, it is inconvenient to use the same.

Disclosure of Invention

Accordingly, it is an object of the present invention to provide an air cleaner capable of overcoming the problems encountered in the conventional art.

It is another object of the present invention to provide an air cleaner capable of quickly cleaning air in a larger area in an improved air circulation construction in which a body of an air cleaner is formed in a cylindrical shape, and air is sucked through an entire surface of a cylindrical body, and the sucked air is passed through a cylindrical filter and a cleaning unit, and the cleaned air is discharged in an upward direction, and in addition it is possible to prevent inlet air and outlet air from being mixed each other for thereby achieving an effective cleaning operation.

It is further another object of the present invention to provide an air cleaner capable of providing not only an air filtering function but also a gas

removing function and a sterilization function for thereby achieving a good quality air.

It is still further another object of the present invention to provide an air cleaner capable of providing a desired warm-air heating without additionally using a heating apparatus when it is needed to increase an indoor temperature.

It is still further another object of the present invention to provide an air cleaner capable of enhancing a convenience of use in such a manner that an operation is automatically performed by setting a cleaning time, and there is provided a wireless remote control function.

To achieve the above objects, there is provided an air cleaner, comprising a cylindrical body fixed to a bottom circular disc wherein an entire appearance of the same is formed of a grill part; a filter unit including a non-woven fabric filter provided in an inner side of the grill part of the cylindrical body, and a cylindrical filter cartridge having a cylindrical wrinkle filter in an inner side; an air inlet guide installed in the interior of the filter unit and having an air inlet part in a lower side wherein an upper side of the same is wide, and a lower side of the same is narrow like a reverse conical shape; an air supply unit assembly including a support circular disc having an air hole and a protrusion part at a center for covering the upper sides of the cylindrical body, the filter unit and the air inlet guide, a motor fixed to the protrusion part of the support circular disc, a fan fixed to a rotary axis of the motor, and a fan housing having an air discharge hole formed along a rim of an upper side surface, while surrounding the fan; a

top housing assembled to an upper side surface of the air supply unit assembly and having a controller with an operation knob in an upper side surface, and a handle wherein a rotation discharge guide part corresponding to the air discharge hole is formed along the rim; and an electronic circuit substrate provided between an upper side of the air supply unit assembly and a lower surface of the top housing.

Brief Description of Drawings

The preferred embodiments of the present invention will be described with reference to the accompanying drawings.

Figure 1 is a perspective view illustrating an air cleaner according to the present invention;

Figure 2 is an entire cross sectional view illustrating an air cleaner according to the present invention;

Figure 3 is a plane cross sectional view illustrating an air cleaner according to the present invention;

Figure 4 is a disassembled perspective view illustrating a filter unit according to the present invention;

Figure 5 is a disassembled cross sectional view illustrating major elements of the present invention;

Figure 6 is a bottom perspective view illustrating an air inlet guide according to the present invention;

Figure 7 is a view illustrating the construction of a support circular disc;
and

Figure 8 is a view illustrating the construction of a fan housing of an electric heater according to the present invention.

Best Mode for Carrying Out the Invention

The construction and operation of the present invention will be described with reference to the accompanying drawings.

Figure 1 is a perspective view illustrating an air cleaner according to the present invention, Figure 2 is an entire cross sectional view, and Figure 3 is a plane cross sectional view.

The air cleaner according to the present invention includes a cylindrical body 110, a filter unit 120 and an air inlet guide 130 in the interior of the cylindrical body, an air supply unit assembly 140 and a top housing 150 installed in an upper side of the cylindrical body.

The cylindrical body 110 is assembled in such a manner that it is assembled on a bottom circular disc 111 having a rubber support 113 in a lower portion of the same. An entire appearance of the cylindrical body is formed of a grill part 112, so that air is sucked through the entire portions in all directions.

In addition, the filter unit 120 comprises a non-woven fabric filter 122 provided in an inner side of the grill part 112 of the cylindrical body 110, and a filter cartridge 121 installed in the inner side of the non-woven fabric filter 122.

The filter cartridge 121 comprises a wrinkle filter 121a, a carbon filter 121b being adherent to the inner surface of the wrinkle filter 121a, and a nano-silver filter 121c being adherent to the inner surface of the carbon filter 121b.

Here, the non-woven fabric filter 122 is formed of a common filter
5 capable of filtering large-size foreign material.

The wrinkle filter 121a is constructed in such a manner that it is wrinkled along a cylindrical circumferential surface in a zigzag shape, for thereby achieving a good filtering ability based on its larger air contact area.

The carbon filter 121b provided in the interior of the wrinkle filter 121a is
10 made in such a manner that active carbon is carburized for thereby first filtering harmful gas.

The nano-silver filter 121c is made in such a manner that silver particles of a nano unit are filled in the holes of the non-woven fabric for thereby finally filtering harmful fungus and smell contained in air.

15 Therefore, the air is filtered in the sequence of the non-woven fabric filter 122 of the first state, the wrinkle filter 121a of the second state, the carbon filter 121b of the third stage and the nano-silver filter 121c of the fourth stage.

The air inlet guide 130 is provided in the interior of the center of the filter unit 120 and is formed in a reverse conical shape wherein the upper side is
20 wide, and the lower side is narrow. The air inlet part 131 has a radial wing part 132 for guiding the flow of air to turbulence flow (whirlwind).

In addition, the air supply unit assembly 140 comprise a support circular

disc 141 that covers the upper sides of the cylindrical body, the filter unit and the air inlet guide and has an air hole 141a and a protrusion part 141b at the center, a motor 142 fixed to the protrusion part of the support circular disc, a fan 143 installed at a rotary axis 142a of the motor, and a fan housing 144 that surrounds the fan 143 and has an air discharge hole 144a formed along a rim of the upper surface.

At this time, as shown in Figure 8, the air supply assembly 140 includes a plurality of electric heaters 160 in an inner side of the air discharge hole 144a.

In addition, as shown in Figure 5, there is provided a sensor cover part 145 extended in the lower direction of one side, and a dust density detection sensor 170 is provided in the interior of the sensor cover part 145 for thereby detecting a dust pollution of the indoor.

As shown in Figure 2 or 5, a sensor hole 144b is formed in one side of the fan housing 144, and a gas density detection sensor 180 and a temperature detection sensor 190 are installed in the inner side for thereby detecting pollution level of a harmful gas and temperature of the indoor.

As shown in Figure 7, an ultraviolet ray sterilizer 220 having a pair of ultraviolet ray lamp 221 is provided on a bottom of the support circular disc 141 for thereby sterilizing the air filtered by the filter unit 120.

In addition, an air guide member 146 is provided in the interior of the air supply unit assembly 140 for guiding the air flowing from the air hole 141a to an air discharge hole 144a in the upper direction, not the bottom direction.

As shown in Figure 2, a transparent grill 148 is provided in a fan housing 144 in the interior of the front side. A wireless receiving unit 147 is provided in the interior of the same for thereby achieving a remote control using a wireless remote controller 300.

5 The top housing 150 is assembled to an upper side of the air supply unit assembly, and a rotation discharge guide part 151 corresponding to the air discharge hole 144a is formed along the rim of the fan housing. A controller 153 having an operation knob 152 and a handle 154 are provided in the upper side.

As shown in Figure 8, an electronic circuit substrate 200 is provided in
10 an upper side of the air supply unit assembly 140 between the lower surfaces of the top housing 150.

Here, the electronic circuit substrate 200 is not described in detail, but it is connected with the power, the operation knobs 152 of the top housing 150, the dust density detection sensor 170 of the sensor cover part 145, the gas
15 density detection sensor 180 of the sensor hole 144b, and the temperature detection sensors 190. In addition, the wireless receiving unit 147 is connected thereto, so that the system is operated by a signal of the wireless remote controller 300.

In addition, an ion generator 210 is provided in one side of the
20 electronic circuit substrate 200, and the ion discharge hose 211 is exposed from one side of the controller 153 to the outside, so that the generated ions are included in the cleaned air.

In Figure 1, reference numeral 155 represents an engaging ring for attaching and detaching the air supply unit assembly 140 onto/from the cylindrical body.

In the air cleaner according to the present invention, when the power is supplied for cleaning the indoor air, the motor 142 is driven and the fan 143 is rotated.

When the fan 143 is rotated, since the air in the interior of the air inlet guide 130 is upwardly moved by the rotation force, and an external air of the cylindrical body 110 is inputted through the grill part 112 and is cleaned when passing through the non-woven fabric filter 122, the wrinkle filter 121a, the carbon filter 121b, and the nano filter 121c. In a state that the air is cleaned, the air is discharged to the rotation discharge guide part 151 of the top housing 150 through the air supply unit assembly 140.

In the present invention, the air circulation is enhanced in such a manner that since the wings of the grill part 112 of the cylindrical body 110 are inclined at a certain angle, the air near the floor of the indoor are sucked, and the air is discharged to the top housing in the upward direction. Therefore, the air just cleaned and discharged is not sucked again.

In addition, the wrinkle filter 121a is formed in a cylindrical shape and has a certain wrinkle width and is wrinkled in a zigzag shape for thereby enhancing a filtering effect by increasing the touch area with the air. As shown in Figure 4, since the carbon filter 121b having an active carbon and the nano

silver filter 121c having silver particles are installed in the double structure, so that a harmful gas, bacteria and smell contained in the air are cleaned.

In particular, as shown in Figure 6, in the air inlet guide 130 of the present invention, the upper side is wide, and the lower side is narrow. In addition, there is provided a turbulence generating wing part 132 in the air inlet part 131, so that the air inputted through the air inlet part 131 is discharged in the upward direction in a turbulence state. Therefore, in the present invention, an air cleaning function is enhanced based on a gas cyclon effect (that is achieved based on a certain apparatus or a function by which floating solid particles of a few μm or a few hundreds μm are separated using a turbulence gas centrifugal force).

After the filtering operation is performed, the air discharged is discharged through the rotation discharge guide part 151 of the top housing 150. Here, since small wing parts 151a of the rotation discharge guide part are inclined at a certain angle, the air is discharged in the upward direction in a radial shape.

Since the dust density detection sensor 170 is provided in the interior of the sensor cover part 145 of the present invention, when the indoor air is polluted above a default value of the sensor, the system is automatically operated.

In addition, since the temperature detection sensor 190 is provided in the interior of the fan housing 144, when the temperature of the indoor air is low,

the electric heater 160 is operated for thereby heating and discharging the air cleaned. Using the gas density detection sensor 180, the presence state and density of the gas are checked. If needed, the ultraviolet ray sterilizer 220 is operated automatically.

5 The ion generator 210 is provided in the interior of the top housing 150, so that the anion can be included in the cleaned and discharged air by operating the operation knob.

Industrial Applicability

10 As described above, in the present invention, the entire structure of the air cleaner according to the present invention is formed in a cylindrical shape. In addition, it is designed in such a manner that the air is sucked through the entire surface of a cylindrical body and the cleaned air is discharged in the upward direction. Therefore, the air of larger spaces is fast cleaned, and the inlet air and
15 the outlet air are not mixed each other for thereby achieving an effective cleaning operation.

 In addition, in the present invention, there are provided a gas removing function and a sterilization function as well as a filtering function for cleaning air, so that it is possible to achieve a good quality air. There is provided an air
20 heating function implemented using the electric heater, so that it is possible to provide a heated air without additionally using a heating apparatus for going up the temperature of the indoor air. There is a function for setting a cleaning time

period for thereby achieving an automatic operation. All operations are performed using a wireless remote controller, so that the use of the system is very convenient.

As the present invention may be embodied in several forms without departing from the spirit or essential characteristics thereof, it should also be understood that the above-described examples are not limited by any of the details of the foregoing description, unless otherwise specified, but rather should be construed broadly within its spirit and scope as defined in the appended claims, and therefore all changes and modifications that fall within the meets and bounds of the claims, or equivalences of such meets and bounds are therefore intended to be embraced by the appended claims.

Claims:

1. An air cleaner, comprising:

a cylindrical body 110 fixed to a bottom circular disc 111 wherein an entire appearance of the same is formed of a grill part 112;

5 a filter unit 120 including a non-woven fabric filter 122 provided in an inner side of the grill part of the cylindrical body, and a cylindrical filter cartridge 121 having a cylindrical wrinkle filter 121a in an inner side;

an air inlet guide 130 installed in the interior of the filter unit and having an air inlet part 131 in a lower side wherein an upper side of the same is wide,
10 and a lower side of the same is narrow like a reverse conical shape;

an air supply unit assembly 140 including a support circular disc 141 having an air hole 141a and a protrusion part 141b at a center for covering the upper sides of the cylindrical body, the filter unit and the air inlet guide, a motor 142 fixed to the protrusion part of the support circular disc, a fan 143 fixed to a
15 rotary axis 142a of the motor, and a fan housing 144 having an air discharge hole 144a formed along a rim of an upper side surface, while surrounding the fan 143;

a top housing 150 assembled to an upper side surface of the air supply unit assembly and having a controller 153 with an operation knob 152 in an
20 upper side surface, and a handle 154 wherein a rotation discharge guide part 151 corresponding to the air discharge hole 144a is formed along the rim; and

an electronic circuit substrate 200 provided between an upper side of

the air supply unit assembly and a lower surface of the top housing.

2. The cleaner of claim 1, wherein said air supply unit assembly 140 includes a plurality of electric heaters 160 in an inner side of the air discharge
5 hole 144a.

3. The cleaner of claim 1, wherein said air supply unit assembly 140 includes a sensor cover part 145 extended in a lower direction of one side wherein a dust density detection sensor 170 is provided in the interior of the
10 sensor cover part.

4. The cleaner of claim 1, wherein in said air supply unit assembly 140, a sensor hole 144b is formed in one side of the fan housing 144, and a gas density detection sensor 180 and a temperature detection sensor 190 are
15 provided in the inner side of the fan housing.

5. The cleaner of claim 1, wherein said air supply unit assembly 140 includes an air guide member 146 capable of guiding the air flowing from the air hole 141a to the air discharge hole 144a in the upper direction, not the bottom.
20

6. The cleaner of claim 1, wherein said air supply unit assembly 140 includes a ultraviolet ray sterilizer 220 having a pair of ultraviolet rat lamps 221

on the bottom of the support circular disc 141.

7. The cleaner of claim 1, wherein said air inlet part 131 of the air inlet guide 130 comprises a radial wing part 132 for guiding the flow of air to
5 turbulence flow.

8. The cleaner of claim 1, wherein said filter cartridge 121 of the filter unit comprises a wrinkle filter 121a, and a carbon filter 121b being adherent to the inner surface of the wrinkle filter 121a.

10


9. The cleaner of claim 1, wherein said filter cartridge 121 of the filter unit 120 includes a wrinkle filter 121a, a carbon filter 121b being adherent to the inner surface of the wrinkle filter 121a, and a nano silver filter 121c being adherent to the inner surface of the carbon filter 121b.

15

10. The cleaner of claim 1, wherein said top housing 150 includes an ion generator 210 therein, wherein a discharge hose 211 connected with the ion generator is exposed from one side of the controller 153 to the outside.


20


1/8
Fig 1



2/8


Fig 2




3/8
Fig 3

4/8


Fig 4




5/8
Fig 5




6/8
Fig 6



7/8
Fig 7



8/8
Fig 8



INTERNATIONAL SEARCH REPORT

 International application No.
 PCT/KR2004/000727
A. CLASSIFICATION OF SUBJECT MATTER**IPC7 B01D 46/00**

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7 B01D 46/00

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Korean Patents and applications for inventions since 1975

Korean Utility models and applications for Utility models since 1975

Japanese Utility models and applications for Utility models since 1975

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

KIPASS, PAJ, USPTO

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5,753,000 A (Honeywell Consumer Products, Inc.) 19 May 1998 See the whole document	1-10
A	US 3,934,990 A (Stratoflex, Inc.) 27 Jan. 1976 See the whole document	1-10
A	JP 8-131150 A (Kansei Corp.) 28 MAY 1996 See the whole document	1-10
A	JP 2001-205025 A (TOSHIN SERVICE:KK) 31 Jul. 2001 See abstract and claims 1-3	1-10

☐ Further documents are listed in the continuation of Box C.

☐ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

13 DECEMBER 2004 (13.12.2004)

Date of mailing of the international search report

16 DECEMBER 2004 (16.12.2004)

Name and mailing address of the ISA/KR


 Korean Intellectual Property Office
 920 Dunsan-dong, Seo-gu, Daejeon 302-701,
 Republic of Korea

Facsimile No. 82-42-472-7140

Authorized officer

JWA, Seung Kwan

Telephone No. 82-42-481-5560

